



HA8025



HA8038



HA9225



HA12025



HA12038



HA17238



HA15055



HA17251



HA20572



HA22580



HA25489



HA28080

Motor type ○:shaped pole AC motor/◎:capacitor induction motor

電機 ○: 蔽極式電機 / ◎: 電容啟動電機

Size	Model	Motor	Bearing	Rated	Frequency	Rated	Rated	Maximum		Maximum		Sound
		Type	System	VoltHDe		Current	Speed	Air Flow	Static Pressure	Level		
尺寸	機型	電機	轉承	電壓		頻率	電流	轉速	最大風量	最大風壓	噪音	
mm	Part No.	○ / ◎	B / S / F	V	Hz	A	RPM	m³/min	CFM	mm-H₂O	In-H₂O	dBA
□80X80X38	HA8038_1H	○	B / S	110	50/60	13/10	2450/2950	0.74/0.88	26/31	4.3/6.0	0.17/0.24	29/30
□80X80X38	HA8038_2H	○	B / S	230	50/60	13/10	2450/2950	0.74/0.88	26/31	4.3/6.0	0.17/0.24	29/30
□92X92X25	HA9225_1H	○	B / S	110	50/60	15/13	2400/2800	0.85/0.99	30/35	4.0/5.0	0.16/0.20	30/31
□92X92X25	HA9225_2H	○	B / S	230	50/60	15/13	2400/2800	0.85/0.99	30/35	4.0/5.0	0.16/0.20	30/31
□120X120X25	HA12025_1H	○	B / S	110	50/60	19/18	2200/2500	1.80/2.30	64/81	5.0/5.9	0.20/0.23	37/38
□120X120X25	HA12025_2H	○	B / S	230	50/60	19/18	2200/2500	1.80/2.30	64/81	5.0/5.9	0.20/0.23	37/38
□120X120X38	HA12038_1L	○	B / S	110	50/60	11/11	2150/2300	2.21/2.04	72/78	3.30/2.29	0.09/0.13	26/27
□120X120X38	HA12038_2L	○	B / S	230	50/60	11/11	2150/2300	2.21/2.04	72/78	3.30/2.29	0.09/0.13	26/27
□120X120X38	HA12038_1M	○	B / S	110	50/60	15/15	2400/2600	2.40/2.37	79/85	3.56/5.33	0.14/0.21	36/37
□120X120X38	HA12038_2M	○	B / S	230	50/60	15/15	2400/2600	2.40/2.37	79/85	3.56/5.33	0.14/0.21	36/37
□120X120X38	HA12038_1H	○	B / S	110	50/60	21/19	2600/3000	2.57/2.97	91/105	6.35/7.62	0.25/0.30	43/44
□120X120X38	HA12038_2H	○	B / S	230	50/60	21/19	2600/3000	2.57/2.97	91/105	6.35/7.62	0.25/0.30	43/44
Ø172X150X38	HA17238B1H	◎	B	110	50/60	27/28	2800/3200	5.38/6.34	190/224	14.5/17.8	0.57/0.70	53/57
Ø172X150X38	HA17238B2H	◎	B	230	50/60	27/28	2800/3200	5.38/6.34	190/224	14.5/17.8	0.57/0.70	53/57
Ø150X55	HA15055B1H	◎	B	110	50/60	46/44	2700/3000	5.38/6.65	190/235	16.0/17.8	0.63/0.70	49/53
Ø150X55	HA15055B2H	◎	B	230	50/60	46/44	2700/3000	5.38/6.65	190/235	16.0/17.8	0.63/0.70	49/53
Ø172X150X51	HA17251B1H	◎	B	110	50/60	35/32	2700/3000	5.09/5.66	180/200	9.6/12.2	0.38/0.48	50/52
Ø172X150X51	HA17251B2H	◎	B	230	50/60	35/32	2700/3000	5.09/5.66	180/200	9.6/12.2	0.38/0.48	50/52
Ø172X150X51	HA17251B2H	◎	B	110	50/60	27/27	2800/3300	6.23/7.59	220/268	15.5/18.0	0.61/0.71	51/61
Ø172X150X51	HA17251B2H	◎	B	230	50/60	27/27	2800/3300	6.23/7.59	220/268	15.5/18.0	0.61/0.71	51/61
□205X205X72	HA20572_1H	◎	B	110	50/60	65/102	2500/3000	16.4/18.3	580/735	25/28	0.98/1.10	67/71
□205X205X72	HA20572_2H	◎	B	230	50/60	65/102	2500/3000	16.4/18.3	560/630	25/28	0.98/1.10	67/71
□225X225X80	HA22580B2H	◎	B	230	50/60	57/71	2550/2900	14.3/16.1	505/570	18.3/17.5	0.72/0.69	58/60
□225X225X80	HA25489B1H	◎	B	110	50/60	60/67	2150/2000	24.5/22.8	700/630	7.9/8.7	0.31/0.35	54/56
Ø254X89	HA25489B2H	◎	B	230	50/60	60/67	2150/2000	24.5/22.8	700/630	7.9/8.7	0.31/0.35	54/56
Ø254X89	HA25489B1M	◎	B	110	50/60	60/67	1400/1600	17.0/18.8	450/520	6.6/7.9	0.27/0.31	49/51
□280X280X80	HA28080B2H	◎	B	230	50/60	129/152	2500/2650	31/32	1088/1130	17.2/20.6	0.85/0.70	68/70