

EC Axial Fan/ EC轴流风扇



HE8025



HE8038



HE9225



HE9232



HE9238



HE12025



HE12038



HE14025



HE15051



HE17251



HE20060



HE20672



HE25489



HE28090

Motor type ○:shaped pole AC motor/◎:capacitor induction motor

電機 ○: 蔽極式電機 /◎: 電容啟動電機

Size 尺寸	Model 機型	Motor Type 電機	Bearing System 轉承	Rated Voltage 電壓	Frequency Hz 頻率	Rated Speed 轉速	Maximum Air Flow 最大風量	Maximum Static Pressure 最大風壓	Sound Level 噪音
mm	Part No.	○/◎	B / S / F	V	Hz	RPM	m ³ /min CFM	mm-H ₂ O In-H ₂ O	dBA
□80X80X25	HE8025_1H	○	B / S	110	50/60	3000	1.14 40.2	4.57 0.18	38.5
□80X80X25	HE8025_2H	○	B / S	220	50/60	3000	1.14 40.2	4.57 0.18	38.5
□80X80X38	HE8038_1H	○	B / S	110	50/60	5000	1.76 62.3	13.6 0.45	52.1
□80X80X38	HE8038_2H	○	B / S	220	50/60	5000	1.76 62.3	13.6 0.45	52.1
□92X92X25	HE9225_1H	○	B / S	110	50/60	2600	1.59 56	4.05 0.16	35
□92X92X25	HE9225_2H	○	B / S	220	50/60	2600	1.59 56	4.05 0.16	35
□92X92X32	HE9232_1H	○	B / S	110	50/60	3500	1.60 56.66	4.24 0.17	43.7
□92X92X32	HE9232_2H	○	B / S	220	50/60	3500	1.60 56.66	4.24 0.17	43.7
□92X92X38	HE9238_1H	○	B / S	110	50/60	4500	2.45 86.38	12.76 0.50	56
□92X92X38	HE9238_2H	○	B / S	220	50/60	4500	2.45 86.38	12.76 0.50	56
□120X120X25	HE12025_1H	○	B / S	110	50/60	3000	2.66 93.6	8.0 0.31	49
□120X120X25	HE12025_2H	○	B / S	220	50/60	3000	2.66 93.6	8.0 0.31	49
□120X120X38	HE12038_1L	○	B / S	110	50/60	3500	3.80 133.82	13.10 0.52	52.4
□120X120X38	HE12038_2L	○	B / S	220	50/60	3500	3.80 133.82	13.10 0.52	52.4
□120X120X38	HE12038_1M	○	B / S	110	50/60	4500	5.94 209.10	25.5 1.00	64.7
□120X120X38	HE12038_2M	○	B / S	220	50/60	4500	5.94 209.10	25.5 1.00	64.7
□140X140X25	HE14025_1H	○	B / S	110	50/60	1800	2.16 76.10	1.70 0.07	18
□140X140X25	HE14025_2H	○	B / S	220	50/60	1800	2.16 76.10	1.70 0.07	18
Ø150X51	HE15050B1H	◎	B	110	50/60	5000	10.66 375.4	10.66 1.39	71.2
Ø150X51	HE15050B2H	◎	B	220	50/60	5000	10.66 375.4	10.66 1.39	71.2
Ø172X150X51	HE17251B1H	◎	B	110	50/60	5000	10.53 371.86	38.17 1.5	69
Ø172X150X51	HE17251B2H	◎	B	220	50/60	5000	10.53 371.86	38.17 1.5	69
□200X200X60	HE20060_1L	◎	B	110	50/60	2000	9.17 324	10.62 0.42	58.6
□200X200X60	HE20060_2L	◎	B	220	50/60	2000	9.17 324	10.62 0.42	58.6
□200X200X60	HE20060_1M	◎	B	110	50/60	2500	11.55 407.92	16.61 0.65	62.4

□200X200X60	HE20060_2M	◎	B	220	50/60	2500	11.55	407.92	16.61	0.65	62.4
□200X200X60	HE20060_1H	◎	B	110	50/60	3000	13.94	492.43	22.69	0.89	68.5
□200X200X60	HE20060_2H	◎	B	220	50/60	3000	13.94	492.43	22.69	0.89	68.5
Ø206X72	HE20672_1H	◎	B	110	50/60	3000	16.52	583.01	28.11	1.11	65.5
Ø206X72	HE20672_2H	◎	B	220	50/60	3000	16.52	583.01	28.11	1.11	65.5
Ø254X89	HE25489B1H	◎	B	110	50/60	2500	20.95	739.23	21.66	0.85	65.4
Ø254X89	HE25489B2H	◎	B	220	50/60	2500	20.95	739.23	21.66	0.85	65.4
□280X280X90	HE28090B1H	◎	B	110	50/60	2500	32.26	1138.5	20.58	0.82	67.8
□280X280X90	HE28090B2H	◎	B	220	50/60	2500	32.26	1138.5	20.58	0.82	67.8

